



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<p>(51) International Patent Classification ⁶ : H01K 1/46, H01J 5/58</p>	<p>A1</p>	<p>(11) International Publication Number: WO 96/27205 (43) International Publication Date: 6 September 1996 (06.09.96)</p>
<p>(21) International Application Number: PCT/IB96/00126 (22) International Filing Date: 15 February 1996 (15.02.96) (30) Priority Data: 95200508.0 2 March 1995 (02.03.95) EP (34) Countries for which the regional or international application was filed: NL et al. (71) Applicant: PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL). (71) Applicant (for SE only): PHILIPS NORDEN AB [SE/SE]; Kottbygatan 5, Kista, S-164 85 Stockholm (SE). (72) Inventors: MARIEN, Lco, Gustaaf, Joanna, Emiel; Vaartstrasse 3, B-2400 Mol (BE). VAN LIEROP, Franciscus, Henricus; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL). (74) Agent: ROODA, Hans; Internationaal Octrooibureau B.V., P.O. Box 220, NL-5600 AE Eindhoven (NL).</p>		<p>(81) Designated States: CN, JP, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published <i>With international search report.</i></p>
<p>(54) Title: ELECTRIC REFLECTOR LAMP</p> <p>(57) Abstract</p> <p>The electric reflector lamp has a light source (20) in an envelope (21) with a seal (22). The seal has a projection (23) against which a plate (25) rests with its side which faces the light source (20). The seal (22) is secured in the neck (5) of a reflector body (1) by means of cement (27) which is present at the side of the plate (25) which faces away from the light source (20). Thereby, an open passage (28) to the beam-shaping portion (4) of the reflector body (1) exists allowing volatile substances released by the cement (27) to escape when the reflector body (1) is closed by means of a cover (7).</p> <div data-bbox="878 1146 1382 1944"> </div>		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IE	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgyzstan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic of Korea	SD	Sudan
CF	Central African Republic	KR	Republic of Korea	SE	Sweden
CG	Congo	KZ	Kazakhstan	SG	Singapore
CH	Switzerland	LI	Liechtenstein	SI	Slovenia
CI	Côte d'Ivoire	LK	Sri Lanka	SK	Slovakia
CM	Cameroon	LR	Liberia	SN	Senegal
CN	China	LT	Lithuania	SZ	Swaziland
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	LV	Latvia	TG	Togo
DE	Germany	MC	Monaco	TJ	Tajikistan
DK	Denmark	MD	Republic of Moldova	TT	Trinidad and Tobago
EE	Estonia	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	UG	Uganda
FI	Finland	MN	Mongolia	US	United States of America
FR	France	MR	Mauritania	UZ	Uzbekistan
GA	Gabon			VN	Viet Nam

Electric reflector lamp.

The invention relates to an electric reflector lamp comprising:

a hollow reflector body having an axis and an optical center, which reflector body is internally reflectorized and includes a concave, light beam-forming portion between a neck and a light-emission window;

5 a light-transmitting cover which is secured to said reflector body and which closes off the light-emission window;

a lamp cap which is provided with contacts and which is fixed around a free-end portion of the neck;

a light source in a gastight, light-transmitting envelope which includes a
10 seal, said light source being axially arranged in the optical center, and said seal of the envelope having a projection and protruding through an aperture in a plate which bears against the projection, and said seal being fixed in the neck;

current conductors which run from the light source through the neck to the contacts of the lamp cap.

15 Such an electric reflector lamp is known from US-A-5,367,219.

In the known reflector lamp the plate firmly retains the seal of the envelope by means of resilient tags which are arranged along the aperture in this plate. The plate exerts an axial pressure on projections which protrude in the neck. The current conductors are tightly tensioned, which leads to deflection of the plate. Thus, the light source
20 is mounted in the reflector body by mechanical means.

The plate is passed over the relatively narrow seal until it contacts the relatively wide envelope itself. The seal has projections over which the resilient tags of the plate are slid and behind which said tags hook themselves to fix the plate on the seal, against the envelope.

25 The lamp cap of the known lamp comprises a synthetic-resin ring at its open end, where it is provided around the free-end portion of the neck, which ring serves as a lengthening portion and widening portion of the lamp cap. Said ring is a separate part of the lamp cap and is locked in place by the neck and the lamp cap, but it could alternatively be integral with said lamp cap. Said ring serves to make the lamp safe to touch after said

lamp has been placed in a lampholder, due to the fact that the ring is wider than the lamp cap without said ring.

It is a disadvantage of the known lamp that the position of the light source in the reflector body can vary from lamp to lamp. This can be attributed to the fact that said position is governed by the position of the light source in the envelope, more particularly by the position of the light source relative to the plate. In the case of the known lamp it is almost impossible to adjust the position of the light source relative to the reflector body. If the light source is relatively voluminous with relatively large dimensions, such as an M-shaped three-dimensional incandescent body, then this is less problematic than it would be when the light source is in fact cylindrical and relatively small. A relatively great spread in properties of the light beam formed by the lamp is then brought about.

In this type of lamps, the cover can be secured to the reflector body by fusing said parts together. This has the disadvantage that deformation may occur during the fusing process. The parts can alternatively be interconnected in a different manner, for example, using an adhesive such as a fusion glass or a synthetic resin such as an epoxy resin or silicone resin. Adhesives may, however, leave residues such as water in the reflector body, which may adversely affect the reflective power.

The light source can be aligned and secured in the reflector body by filling the space in the neck around the seal with cement, for example lamp cement. However, also after the cement has cured thoroughly it emits volatile constituents which can adversely affect the reflective power. US-A-5,281,889 discloses a reflector lamp in which the neck forms a separate body, and a metal plate with resilient tags, which retains the seal of the envelope, is locked in place between the light beam-forming portion and the neck.

From US-A-5,199,787 a reflector lamp is known in which the light source is positioned in the light beam-forming portion by the current conductors. Shocks and vibrations, however, may lead to an undesirable change in the position of the light source.

In the non-prepublished Patent Application EP-94 20 24 66.2 (PHN 14.978) a description is given of a reflector lamp of the type mentioned in the opening paragraph, in which the seal of the envelope is arranged in the neck, in a ceramic body, to reduce the temperature of said seal during operation of the lamp.

The non-prepublished Patent Application EP-94 20 2457.9 (PHN 14.966) describes a reflector lamp in which the concave, light beam-forming portion constitutes the body of revolution of a tilted branch of a parabola on which axial, flat lanes are superposed.

The non-prepublished Patent Application EP-94 20 06 14.9 (PHN 14.762) describes a reflector lamp in which the concave, light beam-forming portion is a paraboloid near to its top, which merges into a body of revolution of a tilted branch of a parabola. The focal points of both portions are at some distance from each other. The light source is
5 supported by the current conductors.

It is an object of the invention to provide an electric reflector lamp of the type described in the opening paragraph, which is of a simple construction and which enables the light source to be aligned as well as volatile substances to escape from the reflector body.

10 In accordance with the invention, this object is achieved by the fact that the plate bears against the projection with a side facing the light source, the seal is secured in the neck by means of cement which is provided on a side of the plate facing away from the light source, which cement leaves a passage, along the seal, to the light beam-forming portion.

15 The use of cement to secure the seal makes it possible to fix the light source in a predetermined place, because the cement fixes the seal in the position obtained after alignment. The plate forms a stop for the cement, which has a relatively low viscosity when it is provided. Said plate makes it possible to bridge the distance between the seal and the neck with cement and, thus, to fix the seal, although the cement touches only a relatively
20 short axial portion of the seal. By virtue thereof, it can be prevented that the cement flows tangentially around the seal. To provide the seal and the neck circumferentially with cement, it would be necessary to apply the cement in a measured amount at various points on the seal. A favorable effect of said incomplete circumferential tangential flow is, however, that an open passage to the light beam-forming portion of the reflector body is preserved. Volatile
25 substances from the cement and, if applicable, from an adhesive used to secure the cover to the reflector body can be expelled during operation of the lamp, partly as a result of the excess pressure in the reflector body caused by the warmup of the gas. This enables attack on the reflective portion of the body to be counteracted.

The plate can be made of glass or a ceramic material. The lamp can be
30 assembled more easily if the plate is made of metal and comprises tags which are directed towards the lamp cap and which press against the seal. The envelope and the plate can then be handled as a unit, thereby avoiding the risk that the plate loses its position on the seal. As regards the fixation of the light source, these tags are of little importance.

The reproducibility of the position of the plate on the seal is favorably

influenced if the projection is positioned between two tags. The projection then forms a stop for the plate itself and not only for a tag at the plate. The reproducibility is further favorably affected by the presence of a second projection opposite the first projection.

Favorably, the projection or projections extending in the axial direction of
5 the reflector body are positioned on the seal so that the plate in the assembled lamp is surrounded, at least substantially, by the lamp cap. Should the cement mass attack the reflection portion of the reflector body, so that the reflective power is partly lost in some areas, emission of light in said areas cannot take place, and said attack will not be observed.

The light source may be an incandescent body, optionally in a halogen-
10 containing atmosphere, or a discharge path between electrodes in an ionizable medium, for example metal halogenides in an inert gas which may contain mercury. The envelope may be made of glass, for example hard glass, or of glass having an SiO_2 content of at least 95 wt. % such as quartz glass, or of a monocrystalline or polycrystalline material such as aluminium oxide. The light source may be surrounded in the envelope by an internal
15 envelope.

These and other aspects of the invention will be apparent from and elucidated with reference to the embodiments described hereinafter.

20 In the drawings:

Fig. 1 is an axial, sectional view of a lamp and a cut-away view of the lamp cap;

Fig. 2 is a sectional view taken on the line II-II in Fig. 1.

The electric reflector lamp shown in Fig. 1 comprises a hollow reflector
25 body 1 which, in this Figure, is made from moulded glass and which has an axis 2 and an optical center 3. The reflector body is internally reflectorized and comprises a concave light beam-forming portion 4 between a neck 5 and a light-emission window 6. Said reflection portion of the reflector body may be a metal layer, for example of silver or aluminium, or an interference filter. The light beam-forming portion is the body of revolution of a branch of a
30 parabola which has its focal point in the optical center and which is tilted towards the axis. Flat paths are superposed on the surface in the transversal direction. A light-transmitting glass cover 7 is secured, in this Figure with an epoxy resin, to the reflector body and closes off the light-emission window 6. The cover is provided at the inner surface with rings of rounded prisms. A lamp cap 10 comprising contacts 11 is secured around a free-end portion

8 of the neck 5 by indenting it into recesses 9. Said lamp cap may alternatively be secured by means of an adhesive such as a glue. The lamp cap 10 shown comprises a synthetic resin ring 12 at the area where it contacts the neck. The ring 12 is locked into position between the neck 5, in particular axial ridges at the outer surface of the neck which are not shown in the Figure, and the lamp cap. A light source 20 in a gastight, light-transmitting envelope 21, which, in this Figure, is made from quartz glass and which has a seal 22, is axially arranged in the optical center 3. In this Figure, the light source is a discharge path between ends 29 of the current conductors 26 which serve as electrodes in a ceramic discharge vessel 30 which is filled with an inert gas, mercury and metal halogenides. The seal 22 of the envelope 21 has a projection 23 and protrudes through an aperture 24 in a plate 25, which, in this Figure, is made from metal, for example steel or spring steel and which bears against the projection 23, and said seal is secured in the neck 5. Current conductors 26 run from the light source 20 through the neck 5 to the contacts 11 of the lamp cap 10.

The plate 25 bears against the projection 23 of the seal 22 with a side facing the light source 20, said seal being fixed in the neck 5 by means of cement 27 which is provided on a side of the plate 25 facing away from the light source 20. Along the seal 22, said cement 27 leaves an open passage 28 to the light beam-forming portion 4. Volatile substances such as water, which are released after through-hardening of the cement and of the epoxy-resin compound between the reflector body and the cover can escape via said passage.

The plate 25 (also see fig. 2) has tags 25' which are directed towards the lamp cap 10 and which press against the seal 22. The projection 23 on the seal is positioned between two tags 25'. Opposite projection 23 there is a second projection 23'. The plate 25 is surrounded by the lamp cap 10.

CLAIMS:

1. An electric reflector lamp comprising:
 - a hollow reflector body (1) having an axis (2) and an optical center (3), which reflector body is internally reflectorized and includes a concave, light beam-forming portion (4) between a neck (5) and a light-emission window (6);
 - 5 a light-transmitting cover (7) which is secured to the reflector body and which closes off the light-emission window (6);
 - a lamp cap (10) which is provided with contacts (11) and which is fixed around a free-end portion (8) of the neck (5);
 - a light source (20) in a gastight, light-transmitting envelope (21) which
 - 10 includes a seal (22), said light source being axially arranged in the optical center (3), and said seal (22) of the envelope (21) having a projection (23) and protruding through an aperture (24) in a plate (25) which bears against the projection (23), and said seal being fixed in the neck (5);
 - current conductors (26) which run from the light source (20) through the
 - 15 neck (5) to the contacts (11) of the lamp cap (10),
 - characterized in that the plate (25) bears against the projection (23) with a side facing the light source (20), the seal (22) is secured in the neck (5) by means of cement (27) which is provided on a side of the plate (25) facing away from the light source (20), which cement (27) leaves a an open passage (28), along the seal (22), to the light beam-
 - 20 forming portion (4).
2. An electric reflector lamp as claimed in Claim 1, characterized in that the plate (25) is made of metal and comprises tags (25') which are directed towards the lamp cap (10) and which press against the seal (22).
3. An electric reflector lamp as claimed in Claim 2, characterized in that the
- 25 projection (23) is positioned between two tags (25').
4. An electric reflector lamp as claimed in Claim 1 or 2, characterized in that a second projection (23') is situated opposite the projection (23).
5. An electric reflector lamp as claimed in Claim 1 or 2, characterized in that the plate (25) is surrounded, at least substantially, by the lamp cap (10).

1/1




FIG. 1




FIG. 2

INTERNATIONAL SEARCH REPORT

International application No.

PCT/IB 96/00126

A. CLASSIFICATION OF SUBJECT MATTER

IPC6: H01K 1/46, H01J 5/58

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC6: H01K, H01J

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 0414312 A1 (N.V. PHILIPS' GLOEILAMPENFABRIEKEN), 27 February 1991 (27.02.91) --	1-5
A	EP 0543448 A1 (N.V. PHILIPS' GLOEILAMPENFABRIEKEN), 26 May 1993 (26.05.93) -- -----	1-5

☐ Further documents are listed in the continuation of Box C.
 ☒ See patent family annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *B* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

Z document member of the same patent family

Date of the actual completion of the international search 4 June 1996	Date of mailing of the international search report 12 -06- 1996
Name and mailing address of the ISA/ Swedish Patent Office Box 5055, S-102 42 STOCKHOLM Facsimile No. +46 8 666 02 86	Authorized officer Jack Hedlund Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT
Information on patent family members

01/04/96

International application No.
PCT/IB 96/00126

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP-A1- 0414312	27/02/91	JP-A- 3095853 US-A- 5053935	22/04/91 01/10/91
EP-A1- 0543448	26/05/93	CA-A- 2083013 CN-A- 1073299 JP-A- 6060856 US-A- 5367219	19/05/93 16/06/93 04/03/94 22/11/94

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☒ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER: _____**

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.